

xTex™ Supported Camera Equipment

Last updated 2025-02-26

See Supported Camera and Lens for:

[xTex A4 V4](#)

[xTex A4 V3 and V2](#)

[xTex A4 V1 no longer supported](#)

[xTex A2](#)

Camera Power Adaptor: Continuous AC power supply for your Nikon camera.



Must be purchased from Vizoo

Compatible with all listed camera equipment and scanners.

Oldest version supported: xTex A4 V2 (Serial Number: XXXXXX-2-107)

xTex A4 V4

(Serial Number: XXXXXX-4-XXX)



Please note: all additional lenses require a unique adaptor for use with the xTex Scanner. If you purchase an additional lens separately, please contact your Vizoo Sales contact to purchase the required adaptor.

Camera	Lens		
			
Nikon Z7 and Z7 II series	Nikon Nikkor Z 35 mm f/1.8	Nikon Nikkor Z 50mm f/1.8 S	Nikon NIKKOR Z MC 105mm f2,8 VR S
External product link (Nikon.com) z7	External product link (Nikon.com)	External product link (Nikon.com)	External product link (Nikon.com)
External product link (Nikon.com) z7 II			
Nikon's first FX-format mirrorless camera with 45.7 effective MP	approx. 600 dpi resolution ~28 x 19 cm capture area / 11 x 7,5 inches	approx. 900 dpi resolution ~22 x 15 cm capture area / 8,7 x 5,9 inches	approx. 1800 dpi resolution ~11 x 7,5 cm capture area / 4,3 x 2,9 inches
Supported from xTex software version 2.6 and newer			Supported from xTex software version 2.8.1 and higher

xTex A4 V3 or V2

(Serial Number: XXXXXX-3-XXX or XXXXXX-2-XXX)

Camera	Lens		
 Nikon D850 SLR (Body) External link (Nikon.com) 45,7 Megapixels Compatible from xTex software version 181 and higher	 Nikon AF-S Nikkor 35mm 1:1,8G ED External link (Nikon.com) approx. 600 dpi resolution ~28 x 19 cm capture area / 11 x 7,5 inches	 AF-S Micro Nikkor 60mm f/2.8G ED External link (Nikon.com) approx. 1000 dpi resolution ~18 x 12 cm capture area / 7,1 x 4,7 inches	 AF-S VR Micro-Nikkor 105mm f/2.8G IF-ED External link approx. 2000 dpi resolution ~9 x 6 cm capture area / 3,6 x 2,4 inches
 Nikon D810 SLR (Body) External link (Nikon.com) 36,3 Megapixels Compatible with xTex software version 161 and higher			

xTex A2

Nikon Z-series (recommended): Supported from xTex software version 2.6 and newer

Camera	Lens		
			
Nikon Z7 and Z7 II series External product link (Nikon.com) z7 External product link (Nikon.com) z7 II Nikon's first FX-format mirrorless camera with 45.7 effective MP	Nikon Nikkor Z 50mm f/1.8 S External product link (Nikon.com) approx. 350 dpi resolution ~54 x 36 cm capture area / 21 x 14 inches	NIKKOR Z 85 mm 1:1,8 S External product link (Nikon.com) approx. 600 dpi resolution ~35 x 23 cm capture area / 13,8 x 9 inches	Nikon NIKKOR Z MC 105mm f2,8 VR S External product link (Nikon.com) approx. 720 dpi resolution ~29 x 19 cm capture area / 11,4 x 7,5 inches

Nikon D850/D810: For xTex software versions older than 2.6

Camera	Lens		
D850  Nikon D850 SLR (Body) External link (Nikon.com) 45,7 Megapixels Compatible from xTex software version 181 and higher	 50mm F1.4 DG HSM A (Nikon Mount) External link	 AF-S NIKKOR 85 mm 1:1,8G External link	 AF-S VR Micro-Nikkor 105mm f/2.8G IF-ED External link
D810  Nikon D810 SLR (Body) External link (Nikon.com) 36,3 Megapixels Compatible with xTex software version 161 and higher	approx. 350 dpi resolution ~60 x 40 cm capture area / 23,6 x 15,7 inches	approx. 570 dpi resolution ~36 x 24 cm capture area / 14,2 x 9,4 inches	approx. 720 dpi resolution ~29 x 19 cm capture area / 11,4 x 7,5 inches

xTex A4 V1 – No Longer Supported

Camera Power Adaptor: Continuous AC power supply for your Nikon camera.



Nikon Power adapter EP-5B

[External product link \(Nikon.com\)](http://Nikon.com)

Power adaptor for xTex A4 V1 and V2 (Serial Number: XXXXXX-2-107 and older versions)

Camera:

Nikon D800E SLR (Body)

Nikon D800 SLR (Body)

Nikon D5200 SLR (Kit)

Support of those cameras stopped with software version 2.6